



T2

Countertop POS Terminal



Features

- Modem, Ethernet, WIFI, GPRS
- Contactless card, NFC for small amount payment
- Support E-signature



www.tactilion.com

T2

Countertop POS Terminal



Specification

Processor, Model		Cortex A9, 4 cores, 32-Bit CPU; Secure CPU
Memory		256 MB FLASH, 128 Mb RAM
OS		LINUX
Display		2,8" Colorful LCD, 320 x 240 Resistant touchscreen with signature capture functionality (Optional)
Keypad		10 Numeric Keys, 10 Function Keys
Printer		High Speed Thermal Printer, 50mm paper roll
Card Readers	Magstripe	Triple tracks, bi-directional
	Smart Card	EMV & PBOC approved
	Contactless	NFC 13.56MHz, support ISO14443, Type A/B/C, Mifare Card M1 (Optional)
Audio		Buzzer
Card Slots		PSAM: 3 SIM: 1 SD: 1
Communication		Modem / Ethernet GPRS (Optional) / Wi-Fi (Optional)
Device Ports		1 RS-232, 1 Ethernet, 1 USB Host 1 micro-USB, 1 PIN Pad, 1 Telephone line
Security		PCI 4.0
Power & Battery		Input: 100~240V, 50~60HZ, 0.8A Output: 8.5V, 2.5A
Size		L x W x H = 175mm x 81mm x 68mm
Weight		320g
Environmental	Operating temperature	0° to 50° C
	Storing temperature	-20° to 60° C
	Humidity	5% to 95%, non-condensing

Tactilion LLP

Address: Office 4.01, Fetter Lane, London EC4A 18R, United Kingdom

info@tactilion.com / www.tactilion.com