



G3

Mobile Payment POS Terminal



Features

- Specially designed for high-end restaurant, entertainment and photographic studio, etc.
- The pocket-size and 3G-connected payment terminal
- Combining convenience, mobility and ergonomic design
- Fast printer of high resolution 320*240 pixel color screen
- It enables merchants to challenge various transaction



www.tactilion.com

G3

Mobile Payment POS Terminal



Specification (Default)

Processor, Model	Cortex A9, 4 cores, 32-Bit CPU; Secure CPU	
Memory	128 MB Flash, 64 Mb RAM	
OS	LINUX	
Display	2,8" Colorful LCD, 320 x 240 Resistant touchscreen with signature capture functionality (Optional)	
Keypad	10 Numeric Keys, 9 Function Keys	
Printer	High Speed Thermal Printer, 40mm paper roll	
Card Readers	Magstripe	Triple tracks, bi-directional
	Smart Card	EMV & PBOC approved
	Contactless	NFC 13.56MHz, support ISO14443, Type A/B/C, Mifare Card M3 (Optional)
Audio	Buzzer	
Card Slots	PSAM: 2 SIM: 1 SD: 1	
Communication	GPRS / Wi-Fi / CDMA (Optional) / 3G (Optional) / Bluetooth (Optional)	
Device Ports	1 Multi-functions I/O (2 RS-232 + 1 USB-Host + 1 USB Device), micro-USB	
Data Capture	1D Barcode scanner (Optional) 5MP Camera for QR code capture (Optional)	
Security	PCI 4.0	
Power & Battery	1850mAh lithium battery Input: 100~240V, 50~60HZ, 0.8A Output: 8.5V, 2.5A	
Size	L x W x H = 165mm x 80mm x 65mm	
Weight	440g	
Environmental	Operating temperature	-20° to 60° C
	Storing temperature	-20° to 60° C
	Humidity	5% to 95%, non-condensing

Tactilion LLP

Address: Office 4.01, Fetter Lane, London EC4A 18R, United Kingdom
info@tactilion.com / www.tactilion.com